

Imperial Mini pathway luminaires is a special purpose outdoor luminaire, integral model, totally weather proof aesthetically contoured. Improved long lasting protection against ingress of dust / moisture / insects inside optical compartment with top opening facility for maintenance.

Product Description

- Luminaire comprises of specially contoured spun aluminium body featuring high strength and anti corrosion.
- Aluminium Casting crown attachment added for aesthetics.
- Non yellowing, UV stabilised, translucent V acrylic diffuser, Clear V acrylic diffuser / Clear V PC diffuser
- EPDM gasket.
- Suitable for mounting to internally threaded pipe of designation M30.
- Cable entries for through-wiring of mains supply cable.
- Prewired with E27 holder and suitable for operation on 240V, 50Hz single phase ac supply.



Product Benefits

- Top cover opening facility for easy maintenance.
- Functionally versatile, strong and stable.
- Corrosion resistant and easy maintenance.
- Quick installation and low assembly costs.

Area of Application

Gardens, Smaller Roadways, Private driveways, Residential Area Lighting, Courtyards, Public area lighting like parks & Squares

Available Finish

Pure polyester powder coated

- Graphite grey
- Anthracite grey
- Jet black



Diffuser Options



A8 - Translucent Acrylic

A9 - Clear Acrylic

A12 - Clear Polycarbonate



ID	Wattage	A	B
4890 A8/A9/A12	E27	Ø425	401 / 431

Note : A8-V Diffuser Translucent / A9-V Diffuser Clear / A12-V Diffuser Clear (polycarbonate)

Imperial Mini pathway luminaires is a special purpose outdoor luminaire, integral model, totally weather proof aesthetically contoured. Improved long lasting protection against ingress of dust / moisture / insects inside optical compartment with top opening facility for maintenance.

Product Description

- Luminaire comprises of specially contoured spun aluminium body featuring high strength and anti corrosion.
- Aluminium Casting crown attachment added for aesthetics.
- Non yellowing, UV stabilised, Clear V acrylic diffuser / Clear V PC diffuser
- EPDM gasket.
- Luminaire integrated with 30W LED.
- Suitable for mounting to internally threaded pipe of designation M30.
- Cable entries for through-wiring of mains supply cable.
- Integral constant current power supply
- Suitable for operation on 240V, 50Hz single phase ac supply.
- Ordering guide : KL-4891-CCT (Colour Temperature)
- Available CCT : 2700K, 3000K, 4000K, 5700K



Product Benefits

- High luminous efficiency at reduced wattage.
- Functionally versatile, strong and stable.
- Corrosion resistant and easy maintenance.
- Quick installation and low assembly costs.
- Sustainable LED technology offers durability and optimal light output with low power consumption

Area of Application

Gardens, Smaller Roadways, Private driveways, Residential Area Lighting, Courtyards, Public area lighting like parks & Squares

Available Finish

Pure polyester powder coated


- Graphite grey
- Anthracite grey
- Jet black


Diffuser Options



A9 - Clear Acrylic

A12 - Clear Polycarbonate





Technical Specifications

General

ID	: 4891
System Wattage	: 30W LED
Driver Integral	: Constant Current
Input Voltage	: 230 - 240Vac
Frequency	: 50-60Hz
Operating Voltage	: 100-277Vac
Operating Temperature	: -15°C~+50°C

Physical

Body	: Spun Aluminium
Diffuser	: Clear acrylic (A9) / Clear Polycarbonate (A12)
Mounting	: Suitable for mounting to internally threaded pipe of designation M30
Finish	: Powder coated Graphite grey / Jet black Anthracite grey

Light Source


Light Source	: OSRAM / LUMILEDS
CRI (Ra)	: >70
LED Colour Temperature	: 2700K / 3000K / 4000K / 5700K

Driver

Power Supply	: Integral
Power Factor	: >0.95
THD	: <10%
Surge Protection	: 4KV
Efficiency	: >85%

Optical Performance

Optical Distribution	: Type IV
----------------------	-----------



Note : It is our constant endeavor to upgrade the performance of our products. For the latest technical information, IES files and product updates please refer to the website at www.klite.in

Imperial Mini pathway luminaires is a special purpose outdoor luminaire, integral model, totally weather proof aesthetically contoured. Improved long lasting protection against ingress of dust / moisture / insects inside optical compartment with top opening facility for maintenance.

Product Description

- Luminaire comprises of specially contoured spun aluminium body featuring high strength and anti corrosion.
- Pressure die cast aluminium crown attachment added for aesthetics.
- Non yellowing, UV stabilised, translucent V acrylic / translucent convex acrylic diffuser.
- EPDM gasket.
- Luminaire integrated with 30W LED.
- Suitable for mounting to internally threaded pipe of designation M30.
- Cable entries for through-wiring of mains supply cable.
- Integral constant current power supply
- Suitable for operation on 240V, 50Hz single phase ac supply.
- Ordering guide : KL-4892-CCT (Colour Temperature)
- Available CCT : 2700K, 3000K, 4000K, 5700K



Product Benefits

- High luminous efficiency at reduced wattage.
- Functionally versatile, strong and stable.
- Corrosion resistant and easy maintenance.
- Quick installation and low assembly costs.
- Sustainable LED technology offers durability and optimal light output with low power consumption

Area of Application

Gardens, Smaller Roadways, Private driveways, Residential Area Lighting, Courtyards, Public area lighting like parks & Squares

Available Finish

Pure polyester powder coated


- Graphite grey
- Anthracite grey
- Jet black


Diffuser Options



A8 - Translucent Acrylic

A10 - Translucent Acrylic





Technical Specifications

General

ID	: 4892
System Wattage	: 30W LED
Driver Integral	: Constant Current
Input Voltage	: 230 - 240Vac
Frequency	: 50-60Hz
Operating Voltage	: 100-277Vac
Operating Temperature	: -15°C~+50°C

Physical

Body	: Spun Aluminium
Diffuser	: Translucent acrylic
Mounting	: Suitable for mounting to internally threaded pipe of designation : M30
Finish	: Powder coated Graphite grey / Jet black Anthracite grey

Light Source


Light Source	: BRIDGELUX
CRI (Ra)	: >80
LED Colour Temperature	: 2700K / 3000K / 4000K / 5700K

Driver

Power Supply	: Integral
Power Factor	: >0.95
THD	: <10%
Surge Protection	: 4KV
Efficiency	: >85%

Optical Performance

Light Distribution	: Symmetrical
--------------------	---------------



Note : It is our constant endeavor to upgrade the performance of our products. For the latest technical information, IES files and product updates please refer to the website at www.klite.in

Imperial Mini pathway luminaires is a special purpose outdoor luminaire, integral model, totally weather proof aesthetically contoured. Improved long lasting protection against ingress of dust / moisture / insects inside optical compartment with top opening facility for maintenance.

Product Description

- Luminaire comprises of specially contoured spun aluminium body featuring high strength and anti corrosion.
- Aluminium Casting crown attachment added for aesthetics.
- Non yellowing, UV stabilised, Clear V acrylic diffuser / Clear V PC diffuser
- EPDM gasket.
- Luminaire integrated with 50W LED.
- Suitable for mounting to internally threaded pipe of designation M30.
- Cable entries for through-wiring of mains supply cable.
- Integral constant current power supply
- Suitable for operation on 240V, 50Hz single phase ac supply.
- Ordering guide : KL-4893-CCT (Colour Temperature)
- Available CCT : 2700K, 3000K, 4000K, 5700K



Product Benefits

- High luminous efficiency at reduced wattage.
- Functionally versatile, strong and stable.
- Corrosion resistant and easy maintenance.
- Quick installation and low assembly costs.
- Sustainable LED technology offers durability and optimal light output with low power consumption

Area of Application

Gardens, Smaller Roadways, Private driveways, Residential Area Lighting, Courtyards, Public area lighting like parks & Squares

Available Finish

Pure polyester powder coated


- Graphite grey
- Anthracite grey
- Jet black


Diffuser Options



A9 - Clear Acrylic

A12 - Clear Polycarbonate





Technical Specifications

General

ID	: 4893
System Wattage	: 50W LED
Driver Integral	: Constant Current
Input Voltage	: 230-240Vac
Frequency	: 50-60Hz
Operaring Voltage	: 100-277Vac
Opaerating Temperature	: -15°C~+50°C

Physical

Body	: Spun Aluminium
Diffuser	: Clear acrylic (A9) / Clear Polycarbonate (A12)
Mounting	: Suitable for mounting to internally threaded pipe of designation M30
Finish	: Powder coated Graphite grey / Jet black Anthracite grey

Light Source


Light Source	: OSRAM / LUMILEDS
CRI (Ra)	: >70
LED Colour Temperature	: 2700K / 3000K / 4000K 5700K

Driver

Power Supply	: Integral
Power Factor	: >0.95
THD	: <10%
Surge Protection	: 6KV
Efficiency	: >85%

Optical Performance

Optical Distribution	: Type IV
----------------------	-----------



Note : It is our constant endeavor to upgrade the performance of our products. For the latest technical information, IES files and product updates please refer to the website at www.klite.in