

K-LITE

LEVO-R

Power : Upto 40W Upto 80W
Length : 1210mm 2402 mm

Upto
100
lm/w

Features

- Bridgelux / Equivalent LED's
- CRI Ra>80 (>90 On Request)
- SDCM ≤ 3
- L70 / B10 @ 50,000 Hrs



Options

- CCT : 3000K / 4000K / 6000K
- Driver options



Beam Angle




Diffused

RECESS



Dimension
in mm



Housing Colour

- Extruded aluminium with powder coated finish in
RAL9016 White fine texture | RAL9006 Grey fine texture



Open Source

[Light Distribution refer online](#)



Prismatic



PC Opal Matte



Technical Specifications

General

| | |
|-----------------------|--------------------|
| Driver | : Constant Current |
| Input Voltage | : 230-240Vac |
| Frequency | : 50-60Hz |
| Operating Temperature | : -15°C~+50°C |

Physical

| | |
|----------|-------------------------------------|
| Body | : Extruded Aluminium Profile |
| Mounting | : Recess |
| Finish | : White(RAL9016) Grey (RAL 9006) |

Light Source

| | |
|------------------------|--------------------------|
| Light Source | : Bridgelux / Equivalent |
| CRI (Ra) | : >80 (>90 On Request) |
| LED Colour Temperature | : 3000K / 4000K / 6000K |

Driver

| | |
|------------------|--------------|
| Power Supply | : Integrated |
| Power Factor | : >0.90 |
| THD | : <15% |
| Surge Protection | : Upto 3KV |
| Efficiency | : >85% |

Optical

| | |
|-------------------|--|
| Tilt | : Fixed |
| Beam Angle | : 115° |
| Diffuser Material | : PC Opal Matt / Prismatic Diffuser |
| UGR | : <21 |



Ordering Guide

Recess - Opal Matt

| ID | Wattage | C.O.D | Dimension (mm) |
|------|----------|-----------|----------------|
| 2855 | Upto 40W | 1200 x 52 | 1210 x 65 x 35 |
| 2858 | Upto 80W | 2392 x 52 | 2402 x 65 x 35 |

Recess - Prismatic

| ID | Wattage | C.O.D | Dimension (mm) |
|------|----------|-----------|----------------|
| 2852 | Upto 40W | 1200 x 52 | 1210 x 65 x 35 |
| 2853 | Upto 80W | 2392 x 52 | 2402 x 65 x 35 |